

Inshore Div Twilight and Thursday Twilights racing to comply with SYC CATEGORY 7 PLUS

3.07.1	(a) No hatches forward of maximum beam open inwards except if size <0.071m ²		
	(b) Non-conforming hatches labeled 'Not to be opened at sea'		
3.07.2	(a)(i) Hatches above water when heeled 90		
	(a)(ii) Non-conforming hatches; size < 0.07m ²		
	(a)(iii) Non-conforming hatches to be kept shut when racing		
3.08.1	Cockpit strong, self draining and watertight (3.08.2)		
3.20.5	1 X Manual bilge pump if space below floorboards precludes access for bucket bailing.		
3.20.6	Bilge pump not to discharge into closed cockpit		
	Bilge pump not connected to cockpit drains.		
3.23	NAVIGATION LIGHTS		
3.23.1	Navigation lights shall be carried that conform to the International Regulations for Preventing Collisions at Sea (Part C and Technical Annex 1) and shall be exhibited as required by those regulations.		
	Guide to minimum filament bulb power		
	Under 12 m 10 W		
	Tricolour 25 W		
	12 m and above 25 W		
3.23.2	Navigation lights shall be mounted so that they will not be masked by sails or the heeling of the boat.		
3.25.2	A waterproof handheld VHF transceiver or a permanently installed VHF Transceiver.		
4.06.2	1 x Flashlight floating type: Spare batteries and bulbs if replaceable		
4.07.2	First aid Manual		
4.14.1	Night: Emergency Tiller if not tiller steered		
4.14.2	Night: Alternative steering method for rudder loss.		
4.23.1	A 15m - 25m in length heaving line shall be readily accessible to the cockpit. It shall consist of a floating line with a boyant object at one end. The "throwing sock" type is recommended.		
4.26	Retrieval method of crew from water All boats shall be able to demonstrate equipment or method by which crew may be assisted back on board.		